

Research Report No. 85343-CS

A Compendium on Steiner Tree Problems

Editors:

Mathias Hauptmann and Marek Karpinski

Department of Computer Science and
Hausdorff Center for Mathematics

30 July, 2013

This is an online compendium on approximability of the Steiner Tree and related optimization problems.
Address for correspondence: steinerkompendium@cs.uni-bonn.de.

Chapter 1

Steiner Tree Problems

1.1 Minimum Steiner Tree Problem

INSTANCE: Graph $G = (V, E)$, edge costs $c : E \rightarrow \mathbb{R}^+$, set of terminals $S \subseteq V$.

SOLUTION: A tree $T = (V_T, E_T)$ in G such that $S \subseteq V_T \subseteq V$, $E_T \subseteq E$.

COST FUNCTION: $\sum_{e \in E_T} c(e)$

OBJECTIVE: Minimize.

Approx.: Approximable within $\ln 4 + \epsilon < 1.39$ [14] (see also [68],[49]).

Hardness: NP-hard to approximate within an approximation ratio $96/95$ [24].

1.2 Directed Steiner Tree Problem

INSTANCE: Directed graph $G = (V, E)$, edge costs $w : E \rightarrow \mathbb{R}^+$, root $r \in V$, set of terminals $S \subseteq V$ of size $(|S| = k)$.

SOLUTION: A directed tree $T = (V_T, E_T)$ in G rooted at r such that $S \subseteq V_T \subseteq V$, $E_T \subseteq E$.

COST FUNCTION: $\sum_{e \in E_T} w(e)$.

OBJECTIVE: Minimize.

Approx.: Approximable within approximation ratio $O(|S|^\epsilon)$ for every $\epsilon > 0$ [19].

Hardness: For every fixed $\epsilon > 0$ cannot be approximated within ratio $\log^{2-\epsilon} n$, unless $NP \subseteq ZTIME(n^{\text{polylog}(n)})$ [43].

Comment: Admits a $O(l^3 t^{2/l})$ -approximation algorithm with running time $O(t^{2l} n^l)$, for any integer $l \leq n$, where t is the number of terminals. This gives a $O(t^\epsilon / \epsilon^3)$ -approximation algorithm with running time $O(t^{4/\epsilon} / n^{2/\epsilon})$ for any fixed $\epsilon > 0$, and an $O(\log^t)$ -approximation in quasi-polynomial time [77], [53], [54], [42].

1.3 Steiner Tree Problem with Distances 1 and 2

INSTANCE: Metric space (V, d) , set of terminals $S \subset V$, such that for all pairs of vertices $u \neq v$, $d(u, v) \in \{1, 2\}$

SOLUTION: A tree $TT = (V_T, E_T)$ such that $S \subseteq V_T \subseteq V$

COST FUNCTION: $d(T) := \sum_{e=\{u,v\} \in E_T} d(u, v)$

OBJECTIVE: Minimize.

Approx.: Approximable within approximation ratio 1.25 [9].

Hardness: APX- hard.[60],[11]

1.4 Metric Steiner Tree Problem

INSTANCE: A finite metric space (V, d) and set of terminals $S \subseteq V$.

SOLUTION: A tree $T = (V_T, E_T)$ such that $S \subseteq V_T \subseteq V$.

COST FUNCTION: $\sum_{e=\{u,v\} \in E_T} d(u, v)$.

OBJECTIVE: Minimize.

Approx.: Approximable within $\ln 4 + \epsilon < 1.39$ [14] (see also [68],[49]).

Hardness: NP-hard to approximate within an approximation ratio $96/95$ [24].

Comment: Metric Steiner Tree is equivalent to Minimum Steiner Tree.

1.5 Euclidean Steiner Tree Problem

INSTANCE: Finite set $S \subset \mathbb{R}^2$ of terminals.

SOLUTION: A Steiner tree $T = (V_T, E_T)$ for S with $S \subseteq V_T \subset \mathbb{R}^2$.

COST FUNCTION: The Euclidean length $d_2(T) = \sum_{\{u,v\} \in E_T} \|u - v\|_2$ of T , where $\|\cdot\|_2$ denotes the Euclidean Norm in $\mathbb{R}^2$.

OBJECTIVE: Minimize

Approx.: Admits a PTAS [6].

Hardness: NP-hard [6].

Comment: d -dimensional version where $S \subset \mathbb{R}^d$ admits a PTAS for d being constant. For $d = \log(|S|)/\log \log(|S|)$ the problem is APX-hard [72].

1.6 ϵ -Dense Steiner Tree Problem

INSTANCE: Graph $G = (V, E)$, set of terminals $S \subseteq V$ such that each $s \in S$ has at least $\epsilon \cdot |V \setminus S|$ neighbors in $V \setminus S$

SOLUTION: A Steiner tree $T = (V_T, E_T)$ for S in G

COST FUNCTION: length $|E_T|$ of T

OBJECTIVE: Minimize

Approx.: For every $\epsilon > 0$, there exists a PTAS for the ϵ -Dense Steiner Tree Problem [50]. This also yields existence of an efficient PTAS [45]. The $\Psi(n)$ -Subdense Steiner Tree Problem where every terminal has at least $|V \setminus S|/\Psi(n)$ non-terminal neighbors also admits a PTAS for $\Psi(n) = O(\log(n))$ [17].

Comment: So far the problem is not known to be NP-hard in the exact setting.

1.7 Prize-Collecting Steiner Tree

INSTANCE: Graph $G = (V, E)$, cost function $c : E \rightarrow \mathbb{R}^+$, set of terminals $S \subseteq V$, a penalty function $\pi : S \rightarrow \mathbb{R}^+$.

SOLUTION: A tree $T = (V_T, E_T)$ in G such that $S \subseteq V_T \subseteq V$, $E_T \subseteq E$.

COST FUNCTION: $\sum_{e \in E_T} c(e) + \sum_{s \in S \setminus V_T} \pi(s)$.

OBJECTIVE: Minimize.

Approx.: Approximable within $1.9672 - \delta$ for some $\delta > 0$ [5].

Hardness: NP-hard to approximate within $96/95$ [24].

Comment: Admits a PTAS for the special case when G is a planar graph [21].

1.8 Bottleneck Steiner Tree Problem

INSTANCE: Graph $G = (V, E)$, edge costs $c : E \rightarrow \mathbb{R}^+$, set of terminals $S \subseteq V$.

SOLUTION: A tree $T = (V_T, E_T)$ in G such that $S \subseteq V_T \subseteq V$, $E_T \subseteq E$.

COST FUNCTION: $\max_{e \in E_T} c(e)$

OBJECTIVE: Minimize.

Approx.: Can be solved exactly in polynomial time [29][69][28].

1.9 k-Bottleneck Steiner Tree Problem

INSTANCE: Graph $G = (V, E)$, edge costs $c : E \rightarrow \mathbb{R}^+$, set of terminals $S \subseteq V$, positive integer k .

SOLUTION: A tree $T = (V_T, E_T)$ in G such that $S \subseteq V_T \subseteq V$, $E_T \subseteq E$ and $|V_T \setminus S| \leq k$ (at most k Steiner nodes used).

COST FUNCTION: $\max_{e \in E_T} c(e)$

OBJECTIVE: Minimize.

Hardness: NP-Hard to approximate within approximation ratio $2 - \epsilon$ on undirected metric graphs [1]. NP-Hard to approximate within approximation ratio $\sqrt{2} - \epsilon$ in the Euclidean plane [73].

Approx.: Approximable within approximation ratio 2 on undirected metric graphs [1]. Approximable within approximation ratio 1.866 in the Euclidean plane [75].

Comment: For the euclidean case, exact algorithms exist for $k = 1$ and $k = 2$, with time complexity $O(n \log n)$ and $O(n^2)$ respectively [7]. For the special case of the euclidean plane with no edges allowed between two Steiner points, a $\sqrt{2} + \epsilon$ approximation algorithm exists [58].

1.10 Prize-Collecting Bottleneck Steiner Tree Problem

INSTANCE: Graph $G = (V, E)$, edge costs $c : E \rightarrow \mathbb{R}^+$, set of terminals $S \subseteq V$, a penalty function $\pi : S \rightarrow \mathbb{R}^+$.

SOLUTION: Tree $T = (V_T, E_T)$ in G such that $S \subseteq V_T \subseteq V$, $E_T \subseteq E$.

COST FUNCTION: $\max(\max_{e \in E_T} c(e), \max_{v \notin V_T} \pi(v))$

OBJECTIVE: Minimize.

Comment: Connected to the Prize-Collecting Bottleneck Traveling Salesman Problem [44].

1.11 Node-Weighted Steiner Tree

INSTANCE: Graph $G = (V, E)$, set of terminals $S \subseteq V$ and a node weight function $w : V \rightarrow \mathbb{R}^+$.

SOLUTION: A tree $T = (V_T, E_T)$ in G , such that $S \subseteq V_T \subseteq V$, $E_T \subseteq E$.

COST FUNCTION: $\sum_{v \in V_T} w(v)$

OBJECTIVE: Minimize.

Approx.: Approximable within approximation ratio $1.35 \ln k$ [37]. Approximable within approximation ratio $\ln k$ in the unweighted case [37].

Hardness: NP-Hard [63],[27]. NP-hard to approximate within $(1 - \epsilon) \ln(k)$ for every $\epsilon > 0$ [37].

Comment: Node-Weighted Steiner Tree in Unit Disk Graphs is approximable within approximation ratio $(5 + \epsilon)$. Admits a PTAS for the special case when the set of vertices is c -local.

A set of vertices S is called c -local in a node-weighted graph if in the minimum node-weighted spanning tree for S , the weight of longest edge is at most c [57].

1.12 Node-Weighted Generalized Steiner Tree

INSTANCE: Graph $G = (V, E)$, node weight function $w : V \rightarrow \mathbb{R}^+$, proper function $f : P(V) \rightarrow \{0, 1\}$

SOLUTION: A subgraph $F = (V_F, E_F)$ of G such that $E_F \cap \delta(S) \geq f(S)$ for all $S \subseteq V$

COST FUNCTION: $\sum_{v \in V_F} w(v)$

OBJECTIVE: Minimize.

Approx.: Approximable within approximation ratio $1.6103 \ln k$ [37].

Hardness: NP-hard to approximate within $(1 - \epsilon) \ln(k)$ for every $\epsilon > 0$ [37].

1.13 Packing Edge-Disjoint Steiner Trees

INSTANCE: An undirected multigraph $G = (V, E)$, set of terminals $S \subseteq V$.

SOLUTION: A set $\mathcal{T} = \{T_1, \dots, T_m\}$ of Steiner trees T_i for S in G which have pairwise disjoint sets of edges.

COST FUNCTION: $|\mathcal{T}|$

OBJECTIVE: Maximize.

Approx.: Approximable within $O(\sqrt{n} \log n)$, where n denotes the number of nodes [23].

Hardness: Not approximable within $(1-\epsilon) \ln(n)$ unless $NP \subseteq DTIME(n^{\log \log n})$. APX-hard for four terminals [23].

1.14 Packing Directed Node-Disjoint Steiner Trees

INSTANCE: Directed multigraph $G = (V, E)$, set of terminals $S \subseteq V$, root $r \in V$.

SOLUTION: A set $\mathcal{T} = \{T_1, \dots, T_m\}$ of directed Steiner trees T_i for S rooted at r in G with pairwise disjoint sets of Steiner nodes.

OBJECTIVE: Maximize.

Approx.: Approximable within approximation ratio $O(m^{1/2+\epsilon})$, where m denotes the number of edges [23].

Hardness: NP-hard to approximate within $m^{1/3-\epsilon}$ [23].

1.15 Buy-at-Bulk k-Steiner Tree

INSTANCE: Graph $G(V, E)$, set of terminals $S \subseteq V$, root $s \in S$, an integer $k \leq |S|$, a buy cost function $b : E \rightarrow \mathbb{R}^+$, a distance cost $dist : E \rightarrow \mathbb{R}^+$.

SOLUTION: A tree $T = (V_T, E_T)$ in G such that $S \subseteq V_T \subseteq V$, $E_T \subseteq E$, $s \in V_T$, $|S \cap V_T| \geq k$.

COST FUNCTION: $\sum_{e \in T} b(e) + \sum_{T \in S-s} \text{dist}(t, s)$.

OBJECTIVE: Minimize.

Approx.: Approximable within approximation ratio $O(\log^4 n)$ [41].

Hardness: NP- hard to approximate within $c \cdot \log(n)$ for some constant c [41] .

1.16 Shallow-light k -Steiner Tree

INSTANCE: Graph $G = (V, E)$, a set of terminals $S \subseteq V$, a buy cost function $b : E \rightarrow \mathbb{R}^+$, a distance cost $r : E \rightarrow \mathbb{R}^+$, cost bound B and length bound D .

SOLUTION: A tree $T = (V_T, E_T)$ in G such that $S \subseteq V_T \subseteq V$, $E_T \subseteq E$, $s \in V_T$, $|S \cap V_T| \geq k$, such that the diameter under r -cost is at most D and buy cost is at most B .

COST FUNCTION: $\sum_{e \in E_T} b(e)$

OBJECTIVE: Minimize.

Approx.: Admits an $(O(\log^2 n), O(\log^4 n))$ -approximation algorithm [41].

Hardness: NP-hard to approximate within $c \cdot \log(n)$ for some constant c [41].

1.17 General Steiner Tree Star Problem

INSTANCE: Graph $G = (V, E)$, set of terminals $S \subseteq V$, steiner nodes $Y \subseteq V$, the edge weights $c : E \rightarrow \mathbb{R}^+$, cost function $w : Y \rightarrow \mathbb{R}^+$.

SOLUTION: A tree $T = (V_T, E_T)$ in G such that $S \subseteq V_T \subseteq V$, $E_T \subseteq E$, $\forall_{v \in V_T \setminus Y} \deg(v) \leq 1$.

COST FUNCTION: $\sum_{e \in E_T} c(e) + \sum_{v \in Y \cap V_T} w(v)$.

OBJECTIVE: Minimize .

Approx.: Approximable with 5.16 and 5 [51].

Hardness: Includes the Metric Steiner Tree Problem as a special case, hence it is NP-hard to approximate within an approximation ration 96/95 [24].

Comment: Special case where S and Y are disjoint is called the Steiner Tree Star Problem. This is already NP-hard [51].

1.18 Polymatroid Steiner Problem

INSTANCE: Graph $G = (V, E)$, the edge weights $c : E \rightarrow \mathbb{R}^+$, a polymatroid $P = P(V)$.

SOLUTION: A tree $T = (V_T, E_T)$ in G such that $S \subseteq V_T \subseteq V$, $E_T \subseteq E$ and T spans base of P .

COST FUNCTION: $\sum_{e \in E_T} c(e)$

OBJECTIVE: Minimize.

Approx.: Approximable within $O(\log^3 k)$ [16], [19], [22].

Hardness: NP-hard to approximate within $\log^{2-\epsilon} n$ for every $\epsilon > 0$ [43], [16].

Comment: The problem contains the Group Steiner Tree Problem as a special case [16].

1.19 Polymatroid Directed Steiner Problem

INSTANCE: Graph $G = (V, E)$, the edge weights $c : E \rightarrow \mathbb{R}^+$, a polymatroid $P = P(V)$.

SOLUTION: A tree $T = (V_T, E_T)$ in G such that $S \subseteq V_T \subseteq V$, $E_T \subseteq E$, connecting a given root $r \in V$ to all vertices of a least one base of P .

COST FUNCTION: $\sum_{e \in E_T} c(e)$.

OBJECTIVE: Minimize.

Approx.: Approximable within $O(k^\epsilon)$ for any $\epsilon > 0$,
approximable within $O(n^{\lg n})$ in quasi-polynomial time [16], [19].

Hardness: NP-hard to approximate within $\log^{2-\epsilon} n$ for every $\epsilon > 0$ [43], [16]

Comment: The problem contains the Directed Steiner Tree Problem as a special case [16].

1.20 Quality of Service Multicast Tree Problem

INSTANCE: Graph $G = (V, E, l, r)$, source $s \in V$, sets of terminals $S_0, \dots, S_N$ with node rates $r_0, \dots, r_N$ and edge lengths $l : E \rightarrow \mathbb{R}^+$.

SOLUTION: A tree $T = (V_T, E_T)$ in G such that $\bigcup_{i \geq 1} S_i \subseteq V_T \subseteq V$, $E_T \subseteq E$.

COST FUNCTION: $\sum_{e \in E_T} c(e)$, where $c(e) = l(e)r_e$ (see comment).

OBJECTIVE: Minimize.

Approx.: Approximable within 1.960 for the case of two non-zero rates. Approximable within 3.802 for the case of unbounded number of rates [48]. For the case of three non-zero rates, the problem admits an 1.522 approximation algorithm [62] [28].

Hardness: NP-hard to approximate within 96/95 [24].

Comment: $r_0 = 0 < r_1 < r_2 < \dots < r_N$ are the distinct rates. For $i = 1, \dots, N$, S_i denotes the set of all nodes with rate r_i . The cost of an edge in the solution tree T is $c(e) = l(e)r_e$, where r_e (rate of edge e) is the maximum rate in the component $T - e$

1.21 Zero Skew Tree Problem

INSTANCE: Metric space (M, d) , set of sinks $S \subseteq M$, edge costs $cost : E \rightarrow \mathbb{R}^+$.

SOLUTION: A stretched tree $T = (V_T, E_T, \pi, c)$ consisting of an arborescence (V_T, E_T) , a mapping $\pi : V_T \rightarrow M$ such that π is a one-to-one mapping between the leaves of T and S and a cost function $c : E_T \rightarrow \mathbb{R}_+$ such that for every edge (u, v) of T , $c(u, v) \geq d(\pi(u), \pi(v))$ and furthermore, for each pair P, P' of root-to-leaf paths in T , $c(P) = c(P')$.

COST FUNCTION: $\sum_{(u,v) \in E_T} c(u, v)$

OBJECTIVE: Minimize.

Approx.: Approximable within approximation ratio 4 when the root is not fixed as a part of the instance [78]. Approximable within approximation ratio $2e$ if the root is fixed [20].

Hardness: NP-hard [20].

Comment: The complexity of the rectilinear zero skew tree problem is not known. For a fixed tree topology, the problem can be solved in linear time by using the Deferred-Merge Embedding (DME) [12], [18], [30].

1.22 Bounded Skew Tree Problem

INSTANCE: Metric space (M, d) , set of sinks $S \subseteq M$, edge costs $cost : E \rightarrow \mathbb{R}^+$, bound b .

SOLUTION: A stretched tree $T = (V_T, E_T, \pi, c)$ consisting of an arborescence (V_T, E_T) , a mapping $\pi : V_T \rightarrow M$ such that π is a one-to-one mapping between the leaves of T and S and a cost function $c : E_T \rightarrow \mathbb{R}_+$ such that for every edge (u, v) of T , $c(u, v) \geq d(\pi(u), \pi(v))$ and furthermore, for each pair P, P' of root-to-leaf paths in T , $|c(P) - c(P')| \leq b$

COST FUNCTION: $\sum_{(u,v) \in E} cost(u, v)$

OBJECTIVE: Minimize.

Approx.: Approximable within approximation ratio 14 when the root is not fixed as a part of the instance [78]. Approximable within 16.86 when the root is given as part of the input [20].

Hardness: NP-hard [20]. Also NP-hard in the two-dimensional rectilinear case [78].

1.23 Stochastic Steiner Tree Problem

INSTANCE: Graph $G = (V, E)$, the root r , first stage edge costs $c_e \geq 0, \forall e \in E$, inflation parameter σ and probability distribution π on the set of scenarios K , where a scenario k is a set of terminal nodes.

SOLUTION: A subset of edges $E_0 \subseteq E$ to be purchased in the first stage

COST FUNCTION: $\sum_{e \in E_0} c_e + \mathbb{E}[\sum_{e \in E_k} c_e \sigma]$ while $E_0 \cup E_k$ spans $S_k \forall k \in K$, where E_k is the set of edges that have to be bought in the second stage to connect all terminal nodes.

OBJECTIVE: Minimize.

Approx.: Approximable within 3.39 [71], [39].

Hardness: NP-hard.

Comment: In this model there are two separate stages: First stage, where G, r, c_e, σ and π are known. In this stage one must purchase set of edges E_0 that is predicted to be useful for connecting unknown set of vertices k that will be drawn from K according to π . Second stage, where k is revealed, cost of every edge is increased times σ and set of edges E_k has to be bought to connect all terminals. [34], [13].

1.24 Group Steiner Tree Problem

INSTANCE: Graph $G = (V, E)$, edge cost $c : E \rightarrow \mathbb{R}^+$, and sets $S_1, \dots, S_n \subseteq V$, also called groups.

SOLUTION: A tree $T = (V_T, E_T)$ in G which contains at least one terminal from every group S_i

COST FUNCTION: $\sum_{e \in E_T} c(e)$.

OBJECTIVE: Minimize.

Approx.: Approximable within $O(\log^3 n)$. Approximable within $O(\log^2 n)$ if G is a tree [36], [27].

Hardness: Not approximable within $\Omega(\log^{2-\epsilon} n)$ unless NP admits quasipolynomial-time Las Vegas algorithm [43].

Comment: Approximable within $O(\log n \text{polylog} \log n)$ when the graph is planar and each group is the set of nodes on a face [27].

1.25 Fractional Steiner Tree Problem with Profits

INSTANCE: Graph $G = (V, E)$, a cost function $c : E \rightarrow \mathbb{R}^+$, a revenue function $r : V \rightarrow \mathbb{R}^+$, fixed cost $c_0 \geq 0$

SOLUTION: A tree $T = (V_T, E_T)$ in G such that $V_T \subseteq V$, $E_T \subseteq E$.

COST FUNCTION:
$$\frac{\sum_{v \in V_T} r(v)}{c_0 + \sum_{e \in E_T} c(e)}.$$

OBJECTIVE: Maximize.

Hardness: NP-hard [26].

1.26 Budget Steiner Tree Problem with Profits

INSTANCE: Graph $G = (V, E)$, a cost function $c : E \rightarrow \mathbb{R}^+$, a revenue function $r : V \rightarrow \mathbb{R}^+$, budget B .

SOLUTION: A tree $T = (V_T, E_T)$ in G such that $V_T \subseteq V$, $E_T \subseteq E$ and $\sum_{e \in E_T} c(e) \leq B$.

COST FUNCTION: $\sum_{v \in V_T} r(v)$

OBJECTIVE: Maximize.

Approx.: Approximable within $(4 + \epsilon)$ for every $\epsilon > 0$ [56]

Hardness: NP-hard.

1.27 Quota Steiner Tree Problem with Profit

INSTANCE: Graph $G = (V, E)$, a cost function $c : E \rightarrow \mathbb{R}^+$, a revenue function $r : V \rightarrow \mathbb{R}^+$, quota Q .

SOLUTION: A tree $T = (V_T, E_T)$ in G such that $V_T \subseteq V$, $E_T \subseteq E$ and $\sum_{v \in V_T} r(v) \geq Q$.

COST FUNCTION: $\sum_{e \in E_T} c(e)$.

OBJECTIVE: Minimize.

Approx.: Approximable within approximation ratio 2.5 [47].

Hardness: NP-hard to approximate within 96/95 [24].

Comment: The lower bound follows from the fact the the Quota Steiner Tree Problem with Profit contains the Steiner Tree Problem as a special case.

1.28 Steiner Tree Problem in Phylogeny

INSTANCE: $C = 1, \dots, m$ set of Characters, for each $i \in C$, set of states A_i of character i , $S \subseteq A_1 \times \dots \times A_m$ set of species.

SOLUTION: A tree $T = (V_T, E_T)$ with $S \subseteq V_T \subseteq A_1 \times \dots \times A_m$

COST FUNCTION: $\sum_{e=u,v \in E_T} d_H(u, v)$, where d_H denotes the Hamming distance [33].

OBJECTIVE: Minimize.

Approx.: Approximable within approximation ratio $\ln(4) + \epsilon$ for every $\epsilon > 0$ [3],[46].

Hardness: NP-hard [33].

Comment: A phylogeny for a set of n distinct species S is a tree whose leaves are all elements of S and where $S \subseteq V(T) \subseteq A_1 \times \cdots \times A_m$.

1.29 Steiner Tree Problem in Phylogeny with Given Topology

INSTANCE: Set of characters $C = 1, \dots, m$, for each $i \in C$ a set A_i of states of character i , $\lambda: S \rightarrow L(T)$ between S and the set $L(T)$ of leaves of T

SOLUTION: An assignment $a: V(T) \setminus L(T) \rightarrow A_1 \times \cdots \times A_m$.

COST FUNCTION: $\sum_{e=u,v \in E_T} d_H(a(u), a(v))$, where d_H denotes the Hamming distance

OBJECTIVE: Minimize.

Approx.: Admits a PTAS [74].

Comment: This is a special case of the Tree Alignment with a Given Phylogeny.

1.30 Tree Alignment with a Given Phylogeny

INSTANCE: Finite set of strings $S \subset \Sigma^*$ over a given finite alphabet, arborescence T , bijection $\lambda: S \rightarrow L(T)$ between S and the set $L(T)$ of leaves of T , scoring scheme $\mu: (\Sigma \cup \{-\})^2 \rightarrow \mathbb{R}$

SOLUTION: An assignment $a: V(T) \setminus L(T) \rightarrow (\Sigma \cup \{-\})^*$ such that for each internal node u of T , $a(u)$ is an alignment of the strings $a(v)$ assigned to all the children v of u in T

COST FUNCTION: $\sum_{e=u,v \in E_T} \mu(a(u), a(v))$

OBJECTIVE: Minimize.

Approx.: Admits a PTAS when the cost function given by the scoring scheme μ is a metric [74].

Hardness: NP-hard. In the case of general scoring schemes, the problem becomes APX-hard [74].

Comment: Augmenting the construction with a local optimization technique, for each $t > 1$, has a performance ratio $1 + 3/t$ [74].

Chapter 2

Steiner Forest Problems

2.1 Steiner Forest Problem

INSTANCE: Graph $G = (V, E)$, cost function $c : E \rightarrow \mathbb{R}_+$, set of k terminal pairs $S = \{(s_1, t_1), \dots, (s_k, t_k)\}$.

SOLUTION: A forest $F \subseteq E$ such that for all $1 \leq j \leq k$, vertices s_j and t_j are contained in the same connected component of F .

COST FUNCTION: $\sum_{e \in F} c_e$.

OBJECTIVE: Minimize.

Approx.: Approximable within $2 - 1/k$ [2].

Hardness: NP-hard to approximate within $96/95$ [24].

Comment: When G is a planar graph [8] obtained a PTAS.

2.2 k-Steiner Forest Problem

INSTANCE: Graph $G = (V, E)$, cost function $c : E \rightarrow \mathbb{R}_+$, set of demands $D = \{(s_1, t_1), \dots, (s_l, t_l)\}$, integer $k \leq l$.

SOLUTION: A forest F in G such that at least k pairs from D are connected by F .

COST FUNCTION: $\sum_{e \in F} c_e$.

OBJECTIVE: Minimize.

Approx.: Approximable within $O(\min\{n^{2/3}, \sqrt{l}\} \log k)$ [79].

Hardness: NP-hard.

2.3 Steiner Forest with Distances One and Two

INSTANCE: Graph $G = (V, E)$, and a collection $\mathcal{R}$ of subsets $R \subseteq V$ called required sets, where $\bigcup_{R \in \mathcal{R}} R$ is the set of *terminals*.

SOLUTION: A set of unordered node pairs F such that each $R \in \mathcal{R}$ is contained in a connected component of (V, F) .

COST FUNCTION: $|F \cap E| + 2|F - E|$.

OBJECTIVE: Minimize.

Approx.: Approximable within $3/2$ [10].

Hardness: APX-hard.[60],[11]

Comment: G defines a $\{1, 2\}$ -Metric on V where E is the set of node pairs which are at distance one from each other, and all other node pairs are at distance 2

2.4 Directed Steiner Forest (DSF)

INSTANCE: A directed graph $G = (V, E)$, an edge cost function $c : E \rightarrow \mathbb{R}_+$, a collection $D \subseteq V \times V$ of ordered node pairs, and an integer $k = |D|$.

SOLUTION: A subgraph F of G that contains an shortest path for (at least) k pairs $(s, t) \in D$.

COST FUNCTION: $\sum_{e \in F} c_e$.

OBJECTIVE: Minimize.

Approx.: Approximable within $O(n^\epsilon * \min\{n^{4/5}, m^{2/3}\})$ for every $\epsilon > 0$ [32].

Hardness: NP-hard to approximate within $\log(n)^{2-\epsilon}$.

Comment: The k-Directed Steiner Forest (k-DSF) is approximable within $O(k^{1/2+\epsilon})$ for every $\epsilon > 0$ [32].

2.5 Prize-Collecting Steiner Forest

INSTANCE: Graph $G = (V, E)$, set of terminal pairs $S = \{(s_i, t_i)\}_{1 \leq i \leq k}$, cost function $c : E \rightarrow \mathbb{R}_+$, penalty function $\pi : S \rightarrow \mathbb{R}_+$.

SOLUTION: A pair (F, Q) , where F is a forest and $Q \subseteq S$ contains all the terminal pairs that are not connected by F

COST FUNCTION: $c(F) + \pi(Q)$.

OBJECTIVE: Minimize.

Approx.: Approximable within approximation ratio 3 using a primal-dual approach. Approximable within approximation ratio 2.54 by an LP-Rounding algorithm [70],[40].

Hardness: NP-hard to approximate within 96/95 [24].

Comment: PTAS exists for the special case when G is planar graph [21].

2.6 Packing Steiner Forest

INSTANCE: Undirected multigraph $G = (V, E)$, set $\mathcal{S} = \{S_1, \dots, S_t\}$ of pairwise disjoint subsets S_i of V

SOLUTION: A set $\mathcal{F}$ of pairwise edge-disjoint Steiner forests F_i for $\mathcal{S}$ in G

COST FUNCTION: $|\mathcal{F}|$ (the number of Steiner forests)

OBJECTIVE: Maximize.

Approx.: APX [55].

Hardness: NP-hard.

Comment: If each S_i is Qk -edge-connected in G , then there are k edge-disjoint S -forests in G . The best upper bound achieved on Q is 32. This yields the first polynomial time constant factor approximation algorithm for the Steiner Forest Packing problem. [55]

2.7 Stochastic Steiner Forest

INSTANCE: A graph $G = (V, E)$, an edge cost function $c : E \rightarrow \mathbb{R}_+$, a probability distribution π over sets of source-sink pairs $2^{\binom{V}{2}}$, and an *inflation* parameter $\lambda \geq 1$.

SOLUTION: A set of first-stage edges E_0 and for each $D \in 2^{\binom{V}{2}}$, a set of second-stage edges E_D such that (i) the edges in $E_0 \cup E_D$ connect each of the pairs in D .

COST FUNCTION: $\sum_{e \in E_0} c_e + \mathbb{E}_{D \leftarrow \pi} [\sum_{e \in E_D} c_e]$.

OBJECTIVE: Minimize.

Approx.: Approximable within 5 [38][34].

Hardness: NP hard.

Comment: A basic building block is an s -star consisting of a non-terminal c , called the center, s terminals $t_1, \dots, t_s$ and edges $(c, t_1), \dots, (c, t_s)$.

Chapter 3

Broadcast

3.1 Minimum Broadcast Time

INSTANCE: Graph $G = (V, E)$ and a source node $v_0 \in V$.

SOLUTION: A broadcasting scheme. At time 0 only v^0 contains the message that is to be broadcast to every vertex. At each time step any vertex that has received the message is allowed to communicate the message to at most one of its neighbours.

COST FUNCTION: The broadcast time, i.e., the time when all vertices have received the message.

OBJECTIVE: Minimize.

Approx.: Approximable within $O(\log^2 |V| / \log \log |V|)$ [66].

Hardness: NP-hard [35].

Comment: Approximable within $2B$ if the degree of G is bounded by a constant B [66]. Approximable within $O(\log V)$ if G is chordal, k -outerplanar [52]. Approximable within $O(\log |V| / \log \log |V|)$ if G has bounded tree width [61].

3.2 Minimum-Energy Broadcast Tree Problem

INSTANCE: Wireless ad-hoc network $M = (N, L)$ consisting of set of nodes N , location function $L : N \rightarrow \mathbb{Z}_+^2$, for each node $v_i \in N$, k power levels $w_{i,1} \leq w_{i,2} \leq \dots \leq w_{i,k}$, a receiver sensitivity $\vartheta > 0$ propagation function $\gamma : \mathbb{Z}^2 \times \mathbb{Z}^2 \rightarrow \mathbb{R}_+$

SOLUTION: An arborescence $T = (N, E)$, power assignment $p = (p_i)_{v_i \in N}$ with $p_i \in \{w_{i,1}, \dots, w_{i,k}\}$ for all $v_i \in N$ such that for each directed edge $e = (v_i, v_j)$ in T , $p_i - \gamma(L(v_i), L(v_j)) \geq \vartheta$

COST FUNCTION: $\sum_{v_i \text{ non-leaf in } T} p_i$

OBJECTIVE: Minimize.

Approx.: Approximable within $O((k+1)^{1/\epsilon} n^{3/\epsilon})$, where $n = |N|$ is the number of nodes in the wireless network, k is the number of power levels at each node, and ϵ is constant with $0 < \epsilon < 1$ [59].

Hardness: NP-hard [59].

Comment: When every node is equipped with the same type of battery, an approximation algorithm has a better performance ratio than that in the general case setting, and the algorithm takes $O(kn^2 \log n)$ time [59].

3.3 Minimum-Energy Multicast Tree Problem

INSTANCE: Wireless ad-hoc network $M = (N, L)$ consisting of set of nodes N , location function $L : N \rightarrow \mathbb{Z}_+^2$, for each node $v_i \in N$, k power levels $w_{i,1} \leq w_{i,2} \leq \dots \leq w_{i,k}$, a receiver sensitivity $\vartheta > 0$ propagation function $\gamma : \mathbb{Z}^2 \times \mathbb{Z}^2 \rightarrow \mathbb{R}_+$, set of destinations $D \subseteq N$, a source $s \in N \setminus D$

SOLUTION: An arborescence $T = (V, E)$ rooted at s with $D \subseteq V \subseteq N$, power assignment $p = (p_i)_{v_i \in V}$ with $p_i \in \{w_{i,1}, \dots, w_{i,k}\}$ for all $v_i \in V$

such that for each directed edge $e = (v_i, v_j)$ in T , $p_i - \gamma(L(v_i), L(v_j)) \geq \vartheta$

COST FUNCTION: $\sum_{v_i \text{ non-leaf in } T} p_i$

OBJECTIVE: Minimize.

Approx.: Approximable within $O(((k+1)n)^{1/\epsilon}|D|^{2/\epsilon} + kn^2)$ [59].

Hardness: NP-hard [59].

Comment: When every node is equipped with the same type of battery, an approximation algorithm has a better performance ratio than that in the general case setting, and the algorithm takes $O(kn|D|\log|D|)$ time [59].

3.4 Restricted Minimum-Energy Broadcast Problem

INSTANCE: A 4-tuple (G, s, d, K) where $G = (V, E)$ is a simple graph, $s \in V$ is the source node, $d < |V|$, $K < |V|^2$ are positive integers.

SOLUTION: A spanning broadcast tree rooted at s .

COST FUNCTION: Total energy in which each transmission radius is at most d .

OBJECTIVE: Minimize energy, at most K

Hardness: NP-hard [31].

Comment: Proof of NP-completeness of the Restricted Minimum-Energy Broadcast (RMEB) based on reduction from vertex cover problem to RMEB [31].

3.5 Unrestricted Minimum-Energy Broadcast Problem

INSTANCE: A 3-tuple (G, s, K) where $G = (V, E)$ is a simple graph, $s \in V$ is the source node, $K < |V|^2$ is a positive integer.

SOLUTION: A spanning broadcast tree rooted at s .

COST FUNCTION: Total energy

OBJECTIVE: Minimize energy, at most K

Approx.: Optimal solution can be found within $O(n^{k+2})$ [31]

3.6 Minimum Broadcast Cover

INSTANCE: A directed graph $G = (V, E)$, a set P consisting of all power levels at which a node can transmit, edge costs $c_{ij} : E(G) \rightarrow R_+$, a source node $r \in V$, an assignment operation $p_i^v : V(G) \rightarrow P$ and some constant $B \in R_+$.

SOLUTION: A node power assignment vector $A = [p_1^v, p_2^v \dots p_{|V|}^v]$ inducing a directed graph $G' = (V, E')$, where $E' = \{(i, j) \in E : c_{ij} \leq p_i^v\}$, in which there is a path from r to any node of V (all nodes are covered)

COST FUNCTION: $\sum_{i \in V} p_i^v$

OBJECTIVE: Minimize cost, at most B

Approx.: There exists approximation algorithm that achieves the $O(\log N)$ approximation ratio [15].

Hardness: NP-complete [15].

Comment: There exists an approximation algorithm for the general version which achieves approximation ratio of $18 \log N$.

3.7 Minimum-Energy Broadcast Problem in Multi-hop Wireless Networks

INSTANCE: A wireless ad hoc network $M = (N, L)$, a source node s , and a terminal set $D = N - \{s\}$.

SOLUTION: Broadcast a message from any source node to all the other nodes.

COST FUNCTION: Sum of transmission powers at all nodes.

OBJECTIVE: Minimize.

Approx.: For any source s , approximable within $2H(n-1)$ [64].

Hardness: NP-hard [64].

3.8 Quality of Service Multicast Tree

INSTANCE: Graph $G = (V, E, l, r)$, the length function on each edge $l : E \rightarrow R_+$, the rate function on each node $r : V \rightarrow R_+$, source s , sets S_i of terminals with rate r_i

SOLUTION: A tree $T = (V_T, E_T, l, r)$ spanning all terminals.

COST FUNCTION: $\sum_{e \in E_T} l(e)r_e$, where $r_e = \max(r_i, r_j)$.

OBJECTIVE: Minimize.

Approx.: Approximable within 3.802 [48]

Hardness: NP-hard to within an approximation ratio 96/95 [24].

Comment: Approximable within 1.960 for two non-zero rates.

3.9 Min-Power Symmetric Connectivity

INSTANCE: Graph $G = (V, E, c)$, cost function $c : E \rightarrow R_+$, transmission range function $r : V \rightarrow \mathbb{R}^+$, some constant $k \geq 1$.

SOLUTION: A connected graph $T = (V, E_T, c)$ s.t. $r(e_1) \geq c(e)$ and $r(e_2) \geq c(e)$, $e_1, e_2 \in V$.

COST FUNCTION: $\sum_{v \in V} r(v)^k$.

OBJECTIVE: Minimize.

Approx.: PTAS with performance ratio $5/3 + \epsilon$ [65] [4].

Hardness: NP-hard for R^2 [25] and APX-complete for R^3 [25].

Comment: More practical approximation algorithm exist with approximation ratio $11/6$ [4] , [76].

MIN-POWER SYMMETRIC CONNECTIVITY WITH ASYMMETRIC POWER REQUIREMENTS is NP-hard to approximate within $(1 - \epsilon) \ln |V|$ [4].

MIN-POWER SYMMETRIC UNICAST is efficiently solvable in time $O(|E| \log |V|)$ [4]

Bibliography

- [1] A.K. Abu-Affash, P Carmi, and M.J. Katz. Bottleneck Steiner Tree with Bounded Number of Steiner Vertices. In *CCCG*, pages 39–42, 2011.
- [2] A. Agrawal, P. Klein, and R. Ravi. When trees collide: An approximation algorithm for the generalized steiner problem on networks. In *Proceedings of the twenty-third Annual ACM Symposium on Theory of Computing*, pages 134–144. ACM, 1991.
- [3] N. Alon, B. Chor, F. Pardi, and A. Rapoport. Approximate Maximum Parsimony and Ancestral Maximum Likelihood. *IEEE/ACM Transactions on Computational Biology and Bioinformatics*, 7:183–187, 2010.
- [4] E. Althaus, G. Calinescu, I. Mandoiu, S. K. Prasad, N. Tchervenski, and A. Zelikovsky. Power efficient range assignment for symmetric connectivity in static ad hoc wireless networks. *Wireless Networks*, 12(3):287–299, 2006.
- [5] A. Archer, M.H. Bateni, M.T. Hajiaghayi, and H. Karloff. Improved approximation algorithms for prize-collecting Steiner tree and TSP. *SIAM Journal on Computing*, 40(2):309–332, 2011.
- [6] S. Arora. Polynomial time approximation schemes for Euclidean TSP and other geometric problems. *Journal of the ACM*, 45(5):753–782, 1998.
- [7] S.W. Bae, C. Lee, and S. Choi. On exact solutions to the euclidean bottleneck steiner tree problem. *Information Processing Letters*, 110(16):672–678, 2010.
- [8] M. H. Bateni, M. T. Hajiaghayi, and D. Marx. Approximation schemes for steiner forest on planar graphs and graphs of bounded treewidth.

- CoRR*, abs/0911.5143, also appeared in *Journal of the ACM*, 58(5), 2011.
- [9] P. Berman, M. Karpinski, and A. Zelikovsky. 1.25-Approximation Algorithm for Steiner Tree Problem with Distances 1 and 2. *Proc. of the 11th Workshop on Algorithms and Data Structures. LNCS 5664*, pages 86–97, 2009.
 - [10] P. Berman, M.Karpinski, and A. Zelikovsky. A factor $3/2$ approximation for generalized steiner tree problem with distances one and two. *CoRR*, abs/0812.2137, 2008. Also appeared in *Proc. of the 21st International Symposium on Algorithms and Computation*, 6506:15–24, 2010.
 - [11] M. Bern and P. Plassmann. The Steiner problem with edge lengths 1 and 2. *Information Processing Letters*, 32(4):171–176, 1989.
 - [12] K.D. Boese and A.B. Kahng. Zero-skew clock routing trees with minimum wirelength. In *ASIC Conference and Exhibit, 1992., Proceedings of Fifth Annual IEEE International*, pages 17–21. IEEE, 1992.
 - [13] I. Bomze, M. Chimani, M. Junger, I. Ljubić, P. Mutzel, and B. Zey. Solving two-stage stochastic steiner tree problems by two-stage branch-and-cut. *Algorithms and Computation*, pages 427–439, 2010.
 - [14] J. Byrka, F. Grandoni, T. Rothvoß, and Laura Sanità. An improved LP-based Approximation for Steiner Tree. In *Proceedings of the 42nd ACM Symposium on Theory of Computing*, pages 583–592, 2010.
 - [15] M. Čagalj, J.P. Hubaux, and C.C.ENZ. Energy-efficient broadcasting in all-wireless networks. *Wireless Networks*, 11(1):177–188, 2005.
 - [16] G. Calinescu and A. Zelikovsky. The polymatroid steiner problems. *Journal of Combinatorial Optimization*, 9(3):281–294, 2005.
 - [17] J. Cardinal, M. Karpinski, R. Schmied, and C. Viehmann. Approximating subdense instances of covering problems. In *Proceedings of the 6th Latin-American Algorithms, Graphs and Optimization Symposium*, pages 59–65, 2011.
 - [18] T.H. Chao, J.M. Ho, and Y.C. Hsu. Zero skew clock net routing. In *Proceedings of the 29th ACM/IEEE Design Automation Conference*, pages 518–523. IEEE Computer Society Press, 1992.

- [19] M. Charikar, C. Chekuri, T. Cheung, Z. Dai, A. Goel, S. Guha, and M. Li. Approximation algorithms for directed Steiner problems. In *Proceedings of the ninth Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 192–200. Society for Industrial and Applied Mathematics, 1998.
- [20] M. Charikar, J. Kleinberg, R. Kumar, S. Rajagopalan, A. Sahai, and A. Tomkins. Minimizing wirelength in zero and bounded skew clock trees. In *Proceedings of the tenth Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 177–184. Society for Industrial and Applied Mathematics, 1999.
- [21] C. Chekuri, A. Ene, and N. Korula. Prize-collecting steiner tree and forest in planar graphs. *CoRR*, abs/1006.4357, 2010.
- [22] C. Chekuri, G. Even, and G. Kortsarz. A combinatorial approximation algorithm for the group steiner problem. *Discrete Applied Mathematics*, 154(1):15–34, 2006.
- [23] J. Cheriyan and M.R. Salavatipour. Hardness and approximation results for packing Steiner trees. *Algorithmica*, 45(1):21–43, 2006.
- [24] M. Chlebík and J. Chlebíková. The steiner tree problem on graphs: Inapproximability results. *Theor. Comput. Sci.*, 406(3):207–214, 2008.
- [25] A. E. F. Clementi, P. Penna, and R. Silvestri. On the power assignment problem in radio networks. *Electronic Colloquium on Computational Complexity (ECCC)*, 7(54), 2000.
- [26] A.M. Costa, J.F. Cordeau, and G. Laporte. Steiner tree problems with profits. *Information Systems and Operational Research*, 44(2):99–116, 2006.
- [27] E. Demaine, M.T. Hajiaghayi, and P. Klein. Node-weighted steiner tree and group steiner tree in planar graphs. *Automata, Languages and Programming*, pages 328–340, 2009.
- [28] D. Du and X. Hu. *Steiner Tree Problems in Computer Communication Networks*. World Scientific Publishing, 2008.

- [29] C.W. Duin and A. Volgenant. The partial sum criterion for Steiner trees in graphs and shortest paths. *European Journal of Operations Research*, 97:172–182, 1997.
- [30] M. Edahiro. Minimum skew and minimum path length routing in vlsi layout design. *NEC research & development*, 32(4):569–575, 1991.
- [31] Ö. Egecioglu, T.F. Gonzalez, and T.L.F. Gonzalez. Minimum-energy broadcast in simple graphs with limited node power. In *in Proc. IASTED Int. Conf. on Parallel and Distributed Computing and Systems*, pages 334–338, 2001.
- [32] M. Feldman, G. Kortsarz, and Z. Nutov. Improved approximating algorithms for directed steiner forest. In *Proceedings of the twentieth Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 922–931. Society for Industrial and Applied Mathematics, 2009.
- [33] D. Fernández-Baca and J. Lagergren. On the approximability of the steiner tree problem in phylogeny. *Algorithms and Computation*, pages 65–74, 1996.
- [34] L. Fleischer, J. Konemann, S. Leonardi, and G. Schafer. Simple cost sharing schemes for multicommodity rent-or-buy and stochastic steiner tree. In *Proceedings of the thirty-eighth Annual ACM Symposium on Theory of Computing*, pages 663–670. ACM, 2006.
- [35] M.R. Garey and D.S. Johnson. *Computers and Intractability: A Guide to the Theory of NP-completeness*. WH Freeman & Co. New York, NY, USA, 1979.
- [36] N. Garg, G. Konjevod, and R. Ravi. A polylogarithmic approximation algorithm for the group steiner tree problem. In *Proceedings of the ninth Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 253–259. Society for Industrial and Applied Mathematics, 1998.
- [37] S. Guha and S. Khuller. Improved methods for approximating node weighted Steiner trees and connected dominating sets. *Information and Computation*, 150(1):57–74, 1999.
- [38] A. Gupta and A. Kumar. A constant-factor approximation for stochastic steiner forest. In *Proceedings of the 41st Annual ACM Symposium on*

Theory of Computing, STOC '09, pages 659–668, New York, NY, USA, 2009. ACM.

- [39] A. Gupta, M. Pál, R. Ravi, and A. Sinha. Boosted sampling: Approximation algorithms for stochastic optimization. In *Proc. of the thirty-sixth Annual ACM Symposium on Theory of Computing*, pages 417–426, 2004.
- [40] M.T. Hajiaghayi and Kamal Jain. The prize-collecting generalized steiner tree problem via a new approach of primal-dual schema. In *Proceedings of the seventeenth Annual ACM-SIAM Symposium on Discrete Algorithm*, pages 631–640, 2006.
- [41] M.T. Hajiaghayi, G. Kortsarz, and M. Salavatipour. Approximating Buy-at-Bulk and Shallow-light k-Steiner trees. *Approximation, Randomization, and Combinatorial Optimization. Algorithms and Techniques*, pages 152–163, 2006.
- [42] E. Halperin, G. Kortsarz, R. Krauthgamer, A. Srinivasan, and N. Wang. Integrality ratio for group steiner trees and directed steiner trees. In *Proceedings of the fourteenth Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 275–284. Society for Industrial and Applied Mathematics, 2003.
- [43] E. Halperin and R. Krauthgamer. Polylogarithmic inapproximability. In *Proceedings of the thirty-fifth Annual ACM Symposium on Theory of Computing*, pages 585–594. ACM, 2003.
- [44] F. Hargesheimer. A Note on the Prize Collecting Bottleneck TSP and Related Problems. *CS Report 85336*, University of Bonn, 2013.
- [45] M. Hauptmann. On the Approximability of Dense Steiner Problems. *Journal of Discrete Algorithms*, 21:41–51, 2013.
- [46] M. Hauptmann and M Lamp. Approximability of Selected Phylogenetic Tree Problems. *CS Report 85299*, University of Bonn, 2008. Also submitted to the Journal of Discrete Algorithms.
- [47] D.S. Johnson, M. Minkoff, and S. Phillips. The prize collecting steiner tree problem: theory and practice. In *Proceedings of the eleventh Annual*

- ACM-SIAM Symposium on Discrete Algorithms*, pages 760–769. Society for Industrial and Applied Mathematics, 2000.
- [48] M. Karpinski, I. Mandoiu, A. Olshevsky, and A. Zelikovsky. Improved Approximation Algorithms for the Quality of Service Steiner Tree Problem. *Proc. of the 8th Workshop on Algorithms and Data Structures. LNCS 2748*, pages 401–411, 2003.
 - [49] M. Karpinski and A. Zelikovsky. New Approximation Algorithms for the Steiner Tree Problems. *Journal of Combinatorial Optimization*, 1(1):47–65, 1997.
 - [50] M. Karpinski and A. Zelikovsky. Approximating dense cases of covering problems. In *Network Design: Connectivity and Facilities Location (Princeton, NJ, 1997)*, volume 40 of *DIMACS Ser. Discrete Math. Theoret. Comput. Sci.*, pages 169–178. 1998.
 - [51] S. Khuller and A. Zhu. The general Steiner tree-star problem. *Information Processing Letters*, 84(4):215–220, 2002.
 - [52] G. Kortsarz and D. Peleg. Approximation algorithms for minimum-time broadcast. *SIAM Journal on Discrete Mathematics*, 8(3):401–427, 1995.
 - [53] G. Kortsarz and D. Peleg. Approximating the weight of shallow Steiner trees. *Discrete Applied Mathematics*, 93(2-3):265–285, 1999.
 - [54] Y. Lando and Z. Nutov. Inapproximability of survivable networks. *Theoretical Computer Science*, 410(21-23):2122–2125, 2009.
 - [55] L.C. Lau. Packing Steiner Forests. *Integer Programming and Combinatorial Optimization*, pages 362–376, 2005.
 - [56] A. Levin. A better approximation algorithm for the budget prize collecting tree problem. *Operations Research Letters*, 32(4):316 – 319, 2004.
 - [57] X. Li, X.H. Xu, F. Zou, H. Du, P. Wan, Y. Wang, and W. Wu. A PTAS for Node-Weighted Steiner Tree in Unit Disk Graphs. *Combinatorial Optimization and Applications*, pages 36–48, 2009.
 - [58] Z.M. Li, D.M. Zhu, and S.H. Ma. Approximation algorithm for bottleneck steiner tree problem in the euclidean plane. *Journal of Computer Science and Technology*, 19(6):791–794, 2004.

- [59] W. Liang. Constructing minimum-energy broadcast trees in wireless ad hoc networks. In *Proceedings of the 3rd ACM International Symposium on Mobile ad hoc Networking & Computing*, pages 112–122. ACM, 2002.
- [60] C. Lung Lu, C. Yi Tang, and R. Chia-Tung Lee. The full steiner tree problem. *Theoretical Computer Science*, 306:55–67, 2003.
- [61] M.V. Marathe, R. Ravi, R. Sundaram, SS Ravi, D.J. Rosenkrantz, and H.B. Hunt III. Bicriteria network design problems. *Arxiv preprint cs/9809103*, 1998.
- [62] P. Mirchandani. The multi-tier tree problem. *INFORMS Journal on Computing*, 8(3):202–218, 1996.
- [63] A. Moss and Y. Rabani. Approximation algorithms for constrained node weighted steiner tree problems. *SIAM J. Comput.*, 2(37):460–481, 2007.
- [64] I. Papadimitriou and L. Georgiadis. Minimum-energy broadcasting in multi-hop wireless networks using a single broadcast tree. *Mobile Networks and Applications*, 11(3):361–375, 2006.
- [65] H. J. Prömel and A. Steger. A new approximation algorithm for the steiner tree problem with performance ratio $5/3$. *J. Algorithms*, 36(1):89–101, 2000.
- [66] R. Ravi. Rapid rumor ramification: Approximating the minimum broadcast time. *Proc. of the 35th Annual Symposium on Foundations of Computer Science*, pages 202–213, 1994.
- [67] G. Robins and A. Zelikovsky. Improved Steiner tree approximation in graphs. In *Proceedings of the eleventh Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 770–779. Society for Industrial and Applied Mathematics, 2000.
- [68] G. Robins and A. Zelikovsky. Tighter Bounds for Graph Steiner Tree Approximation. *SIAM J. Discrete Math.*, 1(19):122–134, 2006.
- [69] M. Sarrafzadeh and C.K. Wong. Bottleneck Steiner trees in the plane. *IEEE Transactions on Computers*, 41(3):370–374, 1992.

- [70] Y. Sharma, C. Swamy, and D.P. Williamson. Approximation algorithms for prize collecting forest problems with submodular penalty functions. In *Proceedings of the eighteenth Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 1275–1284. Society for Industrial and Applied Mathematics, 2007.
- [71] C. Swamy and D.B. Shmoys. Approximation algorithms for 2-stage stochastic optimization problems. *ACM SIGACT News*, 37(1):33–46, 2006.
- [72] L. Trevisan. When Hamming meets Euclid: The approximability of geometric TSP and MST. *SIAM J. on Computing*, 2(30):475–485, 2001.
- [73] L. Wang and D.Z. Du. Approximations for a bottleneck steiner tree problem. *Algorithmica*, 32(4):554–561, 2002.
- [74] L. Wang, T. Jiang, and E.L. Lawler. Approximation algorithms for tree alignment with a given phylogeny. *Algorithmica*, 16(3):302–315, 1996.
- [75] L. Wang and Z. Li. An approximation algorithm for a bottleneck k-steiner tree problem in the euclidean plane. *Information Processing Letters*, 81(3):151–156, 2002.
- [76] A. Zelikovsky. An $11/6$ -approximation algorithm for the network Steiner problem. *Algorithmica*, 9(5):463–470, 1993.
- [77] A. Zelikovsky. A series of approximation algorithms for the acyclic directed Steiner tree problem. *Algorithmica*, 18(1):99–110, 1997.
- [78] A. Zelikovsky and I.I. Măndoiu. Practical approximation algorithms for zero-and bounded-skew trees. In *Proc. of the 12th Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 407–416. Society for Industrial and Applied Mathematics, 2001.
- [79] P. Zhang. An approximation algorithm to the k-steiner forest problem. *Theory and Applications of Models of Computation*, pages 728–737, 2007.

□

Acknowledgement

We acknowledge valuable help and support throughout the editorial process of the following people: Bashir Saad Alvi, Irina Bostan, Gufron Athokjaev, Marc Burdon, Mateusz Łukomski, Fabian Hargesheimer.

Special thanks go to Ignatios Souvatzis for the technical support during the editing process.